

We use cookies to ensure that we can provide you with the best experience on our website. If you continue we assume you consent to receive all cookies from this website. [More Info](#)

**Price: Enquire Today**

[Settings](#)

[Continue](#)



New pump design provides faster UV resin injection  
Improved recoat length and fibre centring repeatability  
Easy user exchangeable mould, inserts and shims for precise concentricity in any application  
RFID technology – recoat mode suggestion capability



Overview

Features

Our high-quality optical fibre recoaters are used to recoat the primary coating of an optical fibre. In applications with flexible packaging requirements, high strength and high reliability splices, softer coatings for gyroscope splices, low-index coatings for power delivery, and more.

Our latest recoaters improve on their respective predecessors in numerous ways. The time to inject recoat material has been reduced by over 50% due to an improved pumping mechanism and new glass mould design. While still utilizing quartz glass, the new mould design improves both pump time and recoat length accuracy, especially for longer recoats, by improving the flow rate of material across the entire mould. The mould also features a unique RFID capability, enabling the FSR to automatically limit selectable recoat modes in the UI, based on mould size installed and recoat mode parameters.

Like its predecessor, the FSR115 has no proof tension.

## Application

Our optical fibre recoaters deliver benefits to a variety of specialty fibre optic industries including:

- Universities
- R&D optical institutes
- High power laser
- Photonics
- Medical applications