

We use cookies to ensure that we can provide you with the best experience on our website. If you continue we assume you consent to receive all cookies from this website. [More Info](#)

**Price: Enquire Today**

**Settings**

**Continue**



Quick splicing time  
Minimal tools  
250µm and/or 900µm fibre capabilities  
Both fibre and coating are secured independently



Overview

Features

Specification

## Our mechanical splice system provides an inexpensive and quick alternative for mating fibres.

Using V-groove and index matching material technology, this splice maintains both the refractive index and physical contact between the fibres. An assembly tool is used to ensure the fibres are mated correctly. The Fujikura mechanical splice secures both fibre and coating independently with the U-shaped sleeve, enhancing the strength against fibre twist.

In its delivery of quick and reliable connections, our mechanical splice system has a maximum insertion loss of less than 0.5dB (average <0.1dB) and return losses greater than 40dB.

Also known as the Universal Mechanical Splice, the mechanical splice can be used for both SI (stepped index) and GI (graded index) fibre with either 250µm or \*900µm coatings. Only the FMSEZ-025/09 system can be used for 900µm diameter fibre.

- FMSEZ-025 (for termination of 250µm fibre)
- FMSEZ-025/09 (for termination of 250µm and 900µm fibre - the 'Universal Mechanical Splice').

### Applications

- Restoration
- Premise environments
- FTTx applications